



DisplayMount Adhesive

Aerosol

TECHNICAL DATA SHEET

Issue 3: Octobre 2007
Supersedes: Feb. 1997

Product Description

Improved 3M DisplayMount™ is a multi purpose adhesive that is specially designed for exhibition, studio and theatre sets, display work and many other applications where heavy duty adhesive is needed.

It is ideal for bonding most porous and non porous materials including many plastics, fabrics, metal foils, paper, board, carpeting and rubber.

The new controlled spray pattern greatly reduces adhesive mist..

Physical Properties

Not for specification purposes

Solvent	Petroleum Distillates, Pentane, Acetone
Flash Point	-46°C (propellant)
Propellant	Propane, Hydrocarbon
Contents	400 ml (293g)
Spray Pattern	Particle
Colour	Clear
Shelf Life	12 months from date of receipt by customer when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity

Additional Product

Information Does not contribute to ozone depletion.



DisplayMount Adhesive

Aerosol

2

Coverage:	Approximately 10m ² (120 square feet) per container, depending on porosity of substrate.		
Storage Conditions	Cool dry place. Best results are obtained when material is stored and applied at room temperature 16 to 27°C. Storage temperature must not exceed 49°C.		
Directions for Use	<p>Ensure all surfaces to be bonded are clean, dry and free from dust, oil and grease before application of adhesive.</p> <p>Ensure that the nozzle points away from all persons and towards the surface to be sprayed. Turn the spray tip so that the arrow points to the dot on the can rim..</p> <p>Shake can well before using, 5-10 seconds should be sufficient.</p> <p>Hold the container 15 to 20 cms from the surface and apply evenly to cover the entire area.</p> <p>For further information please contact your Product Responsibility / Toxicology Department</p>	<p>To bond porous materials (such as paper, board and fabric) apply to one surface only and place in position while the adhesives is still wet. For non porous materials (such as metal foils, plastics and film) spray adhesive onto both surfaces and let adhesive become aggressively tacky before bonding.</p> <p>To prevent nozzle from blocking, at the end of each day turn the can upside down and press the tip until spray is clear from adhesive, and wipe tip.</p>	<p>Clean Up: Spray nozzle or excess adhesive may be cleaned with white spirits. NOTE: When using solvents for clean up, it is essential that proper safety precautions are observed.</p>
Application	<p>DisplayMount™ is extensively used for bonding lightweight boards, plastics, fabric, paper and many other materials.</p> <p>For bonding backcloths in studios and window dressing in exhibition displays and 3D lettering.</p>		
Health and Safety Information	For further information please contact your Product Responsibility / Toxicology Department		

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendation