

Trade name: edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)

Version: 2.0.0 / GB

Status: 06.11.2008

## 1.) Identification of the substance/preparation and of the company/undertaking

### Identification of the substance or preparation

#### Trade name

**edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)  
contained in: edding 3000**

#### Use of the substance/preparation

Refilling ink

### Company/undertaking identification

#### Address

edding Aktiengesellschaft  
Bookkoppel 7  
D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

#### Information provided by / telephone

+49 (0)4102 - 808-0

#### Emergency telephone

+49 (0)30 192 40 (Toxic Substance Emergency Call Centre Berlin)

#### Advice on Safety Data Sheet

sdb\_info@umco.de

## 2.) Hazards identification

### Classification

|        |   |
|--------|---|
| R10    | Flammable.  |
| R52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

### Hazard symbols

- N O N E

### R phrases

|       |   |
|-------|---|
| 10    | Flammable.  |
| 52/53 | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |

## 3.) Composition / information on ingredients

### Chemical characterization

Mixture (preparation)

### Hazardous ingredients

#### 1-METHOXY-2-PROPANOL

|                |           |           |              |         |          |
|----------------|-----------|-----------|--------------|---------|----------|
| EC no.         | 203-539-1 | Index no. | 603-064-00-3 | CAS no. | 107-98-2 |
| Concentration  | > 55      | < 60      | %-b.w.       |         |          |
| Classification | R10       |           |              |         |          |
| Hazard symbols | -         | R phrases | 10           |         |          |

#### Poly(oxy-1,2-ethanediyl), .alpha.-decyl-.omega.-hydroxy-, phosphate

|                |         |           |        |         |            |
|----------------|---------|-----------|--------|---------|------------|
| EC no.         | -       | Index no. | -      | CAS no. | 52019-36-0 |
| Concentration  | > 1     | < 5       | %-b.w. |         |            |
| Classification | Xi; R38 | Xi; R41   |        |         |            |
| Hazard symbols | Xi      | R phrases | 38-41  |         |            |

**alpha, alpha-bis[4-(dimethylamino)phenyl]-4-(phenylamino)naphthalene-1  
methanol, C.I. Solvent Blue 4**

Trade name: edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)

Version: 2.0.0 / GB

Status: 06.11.2008

|                |           |           |          |         |           |
|----------------|-----------|-----------|----------|---------|-----------|
| EC no.         | 229-851-8 | Index no. | -        | CAS no. | 6786-83-0 |
| Concentration  | > 0,5     | < 1       | %-b.w.   |         |           |
| Classification | Xn; R22   | N; R50/53 |          |         |           |
| Hazard symbols | Xn, N     | R phrases | 22-50/53 |         |           |

## Other information (chapter 3.)

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

## 4.) First aid measures

### General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

### After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners !

### After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.).

### After ingestion

Rinse mouth thoroughly with water. Summon a doctor immediately. Never give anything by mouth to an unconscious person.

## 5.) Fire-fighting measures

### Suitable extinguishing media

Alcohol-resistant foam; extinguishing powder; Carbon dioxide; Water spray jet

### Extinguishing media that must not be used for safety reasons

Full water jet

### Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In the event of fire, the following can be released:

Carbon dioxide (CO<sub>2</sub>)

Carbon monoxide (CO)

### Special protective equipment for fire-fighters

Use self-contained breathing apparatus. Wear protective clothing.

### Other information

Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet.

## 6.) Accidental release measures

### Personal precautions

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation. Keep away sources of ignition.

### Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

### Methods for cleaning up/taking up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

Trade name: edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)

Version: 2.0.0 / GB

Status: 06.11.2008

**7.) Handling and storage****Handling****Advice on safe handling**

Provide good ventilation of working area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far as it is possible by the state of the art.

**Advice on protection against fire and explosion**

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

**Storage****Requirements for storage rooms and vessels**

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

**Advice on storage assembly**

Do not store together with:

Acids  
Alcalies  
Oxidizing agents

**Further information on storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

**8.) Exposure controls / personal protection****Exposure limit values****1-METHOXY-2-PROPANOL**

CAS no. 107-98-2  
EC no. 203-539-1

**2000/39/EWG****1-Methoxypropanol-2**

|                                      |      |                   |     |                   |
|--------------------------------------|------|-------------------|-----|-------------------|
| TWA                                  | 375  | mg/m <sup>3</sup> | 100 | ml/m <sup>3</sup> |
| STEL                                 | 568  | mg/m <sup>3</sup> | 150 | ml/m <sup>3</sup> |
| Skin resorption /<br>sensibilisation | Skin |                   |     |                   |

**Occupational Exposure Standards (OESs) / EH40****1-Methoxypropan-2-ol**

|                                      |     |                   |     |                   |
|--------------------------------------|-----|-------------------|-----|-------------------|
| TWA                                  | 375 | mg/m <sup>3</sup> | 100 | ml/m <sup>3</sup> |
| STEL                                 | 560 | mg/m <sup>3</sup> | 150 | ml/m <sup>3</sup> |
| Skin resorption /<br>sensibilisation | Sk  |                   |     |                   |

**Personal protective equipment****Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Trade name: edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)

Version: 2.0.0 / GB

Status: 06.11.2008

## Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

|                      |              |     |      |
|----------------------|--------------|-----|------|
| Appropriate Material | butyl rubber |     |      |
| Material thickness   |              | 0,5 | mm   |
| Breakthrough time    | >            | 240 | min. |

## Eye protection

Safety glasses with side protection shield (EN 166)

## Skin protection

Clothing as usual in the chemical industry.

## General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

## 9.) Physical and chemical properties

### General information

|        |                |
|--------|----------------|
| Form   | liquid         |
| Colour | black          |
| Odour  | characteristic |

### Important health, safety and environmental information

#### Changes in physical state

|          |               |     |    |
|----------|---------------|-----|----|
| Type     | Boiling point |     |    |
| Value    | >             | 100 | °C |
| Pressure | 1013          | hPa |    |

#### Flash point

|        |             |    |      |    |
|--------|-------------|----|------|----|
| Value  | >           | 23 | - 55 | °C |
| Method | Abel-Pensky |    |      |    |

#### Vapour pressure

|                       |    |     |     |
|-----------------------|----|-----|-----|
| Value                 | <  | 110 | kPa |
| Reference temperature | 50 | °C  |     |

#### Density

|                       |      |        |                   |
|-----------------------|------|--------|-------------------|
| Value                 | 0,90 | - 1,40 | g/cm <sup>3</sup> |
| Reference temperature | 20   | °C     |                   |

#### Viscosity

|                       |              |       |     |
|-----------------------|--------------|-------|-----|
| Type                  | Efflux time  |       |     |
| Value                 | 12           | - 222 | sec |
| Method                | DIN cup 4 mm |       |     |
| Reference temperature | 20           | °C    |     |

#### Solvent separation test

|                       |    |    |   |
|-----------------------|----|----|---|
| Value                 | <  | 3  | % |
| Reference temperature | 20 | °C |   |

#### Other information

The physical data is that of the main component/s.

Trade name: edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)

Version: 2.0.0 / GB

Status: 06.11.2008

## 10.) Stability and reactivity

### Materials to avoid

Acids; Alcalis; Oxidizing agents

### Hazardous decomposition products

No hazardous decomposition products known.

## 11.) Toxicological information

### Experience in practice

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness.

Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

### Other information (chapter 11.)

Product specific toxicological data are not known.

## 12.) Ecological information

### Other adverse effects

Ecological data are not available.

Do not discharge product unmonitored into the environment.

## 13.) Disposal considerations

### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

### Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

## 14.) Transport information

### Land transport ADR/RID

|                       |                        |                     |    |
|-----------------------|------------------------|---------------------|----|
| Class                 | 3                      | Classification code | F1 |
| Packaging group       | III                    |                     |    |
| Hazard id. no.        | 30                     |                     |    |
| Label                 | 3                      |                     |    |
| UN number             | 1263                   |                     |    |
| Technical name        | Paint related material |                     |    |
| Special Provision 640 | E                      |                     |    |

### Marine transport IMDG

|                      |                        |
|----------------------|------------------------|
| Class                | 3                      |
| Packaging group      | III                    |
| UN number            | 1263                   |
| Proper shipping name | Paint related material |
| EmS                  | F-E, S-E               |
| MARPOL               | --                     |
| Label                | 3                      |

Trade name: edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)

Version: 2.0.0 / GB

Status: 06.11.2008

**Air transport ICAO/IATA**

|                      |                        |
|----------------------|------------------------|
| Class                | 3                      |
| Packaging group      | III                    |
| UN number            | 1263                   |
| Proper shipping name | Paint related material |
| Label                | 3                      |

**15.) Regulatory information****Labelling in accordance with EC directives**

The product is classified and labelled in accordance with EC Directive 1999/45/EC.

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

**Hazard symbols**

- N O N E

**R phrases**

10 Flammable.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**S phrases**

51 Use only in well-ventilated areas.  
61 Avoid release to the environment. Refer to special instructions / Safety data sheets.

**Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances**

Remarks Annex I, part 2, category 6

**16.) Other information****Sources of key data used to compile the data sheet:**

EC Directive 67/548/EC resp. 99/45/EC as amended in each case.

Regulation (EC) No 1907/2006 (REACH) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC as amended in each case.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

**Relevant R-phrases (chapter 3):**

10 Flammable.  
22 Harmful if swallowed.  
38 Irritating to skin.  
41 Risk of serious damage to eyes.  
50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Department issuing safety data sheet**

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183 b, D-21107 Hamburg

Tel.: +49 40 / 41 92 13 00 Fax: +49 40 / 41 92 13 57 e-mail: umco@umco.de

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Trade name: edding Permanent Marker Refill Ink T25, T100, T1000, MTK25 (black)

Version: 2.0.0 / GB

Status: 06.11.2008