



tesapack® Paper Strong ecoLogo®

Product Information

BNR 05054, 55337, 57180

Product Description

tesapack® packing paper tape. Sustainable and resistant with backing material paper from certified forests and other controlled sources, as well as an adhesive made of natural rubber. Suitable for parcels weighing up to 20 kg. Reliably seals different types of cardboard boxes.

Product Features

- A sustainable contribution: Made with paper from certified forests and other controlled sources
- Versatile adhesive made from natural rubber: Good adhesion to different types of cardboard
- Applications: Strong adhesion for securely sealing packages weighing up to 20 kg
- Carefree parcel tape: Made without solvents
- Practical: Easily unroll the tape by hand or with the help of a dispenser - can be torn by hand
- Recyclability tested using the INGEDE method 12: Does not impact cardboard processing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | Paper | • Total thickness | 125 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------------|--------------------------|-----|
| • Elongation at break | 8 % | • Ageing resistance (UV) | no |
| • Adhesive strength | High adhesion | • Hand tearability | yes |



tesapack® Paper Strong ecoLogo®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>