



# tesa® extra Power Universal (>60% recycled backing)

## Product Information

BNR 56348, 56396, 56389, 56490, 56388

### Product Description

tesa® extra Power Universal is a versatile duct tape with extra bonding power, made with recycled materials. Ideal for handicrafts, repairing, fastening, bundling and marking and more.

### Sustainable Aspects

By incorporating over 60% post-consumer recycled materials into its backing, tesa® extra Power Universal Duct Tape offers a more sustainable option.

### Product Features

- For handicrafts, repairing, fastening, bundling, strengthening, marking and much more
- For daily uncomplicated solutions and quick & easy repairs
- Backing made from more than 60% post-consumer recycled materials - increasing sustainability and reducing waste!
- Very good adhesion to all types of surfaces
- Weather-resistant for in-and outdoor applications
- Tearable by hand
- Solvent-free

### Application Fields

This Duct Tape works best on clean, smooth surfaces. Apply the tape and press firmly onto the surface.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing	PE laminated cloth	• Type of adhesive	synthetic rubber
• Post-consumer recycled content of backing	67 %	• Total thickness	215 µm

# tesa® extra Power Universal (>60% recycled backing)

## Product Information

### Properties/Performance Values

• Elongation at break	16 %	• Hand tearability	good
• Tensile strength	41.2 N/cm	• Humidity resistance	yes
• Abrasion resistance	very good	• Residue-free removability	no
• Adhesive strength	High adhesion	• Solvent free	yes
• Ageing resistance (UV)	yes	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Metal
• Application temperature from	5 °C	• Tear resistance	yes
• Application temperature to	60 °C	• UV resistant	yes
• Area of use	In- and Outdoor	• Writable	yes
• Chemical Resistance	yes		

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>