

Tec 20



| Model | Item no. | | |
|-------|----------|--|--|
|-------|----------|--|--|

Polyamid base, black

with standard gaslift and double-wheel castors

72220

Aluminium base, polished

with standard gaslift and double-wheel castors

72229

Counterversion:

gaslift, medium-high

foot ring

gaslift, high (incl. foot ring and foot glides)

OPTIONS Hard floor castors, item no. 6991 / Foot glides, item no 6988

Fabrics

PU0 (Polyurethane foam)

Dimensions

| | |
|---------------------|----------|
| Seat height: | 41-54 cm |
| Seat height medium: | 50-69 cm |
| Seat height high: | 59-84 cm |
| Seat width: | 46 cm |
| Seat depth: | 43 cm |
| Backrest height: | 30 cm |

Technical data


| | |
|------------------|------------------|
| Weight | approx. 10-12 kg |
| Unit: | 1/carton |
| Pallet quantity: | 16/pallet |



Work swivel chair made of durable polyurethane foam



Seat height adjustable in various positions by safety gaslift




Backrest adjustable in height and depth



FEATURE

Seat and backrest made of durable polyurethane foam, height adjustable in various positions



Decorative and solid, black polyamide base or polished aluminium base, equipped with braked double-wheel safety castors for carpet floors



This product has the GS-sign of Intertek in Fuerth and complies in this relation to all security requirements

Max. user height 1,92 m | Max. user weight 110 kg | Max. using time / day 8 hours