

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Black [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : March 18, 2009

File No. : 010275A Rev. 2.5.06.03

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Carbon Black	1333-86-4	Registered	2156099	< 10
Resin	Registered	Registered	Registered	< 10
Ethylene glycol	107-21-1	Registered	2034733	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10
2-Propanol	67-63-0	Registered	2006617	< 10

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Carbon Black>

MAJOR HEALTH HAZARDS: suspect cancer hazard (in animals)

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

<Resin>

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

<2-Propanol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, eye irritation, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 36.0g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire.

Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

: Keep out of the reach of children.

: Avoid contact with skin and eyes.

Precautions	: Not available.
Safe handling advice	: Not available.
Storage:	
Technical measures	: Keep away from oxidizing materials, ignition sources and high temperature.
Storage condition	: Avoid direct sunlight.
	: Do not leave the products in high temperature space.
	: Recommended temperature: 0-30 C.
Incompatible products	: (Information of components.)
oxidizing materials, halogens	Carbon Black
oxidizing materials	Resin
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials	Ethyl alcohol
acids, metals, oxidizing materials, combustible materials, halogens, peroxides, bases, metal salts	2-Propanol
Packaging materials	: Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	3.5mg/m3 TWA 1000ppm TWA 400 ppm TWA, 500ppm STEL	Carbon Black Ethyl alcohol 2-Propanol
ACGIH	3.5mg/m3 TWA 100mg/m3 ceiling (particulate)(aerosol) 1000ppm TWA 200ppm TWA, 400ppm STEL	Carbon Black Ethylene glycol Ethyl alcohol 2-Propanol
EC	3.5mg/m3 TWA 52mg/m3(20ppm) TWA(skin), 104mg/m3(40ppm) STEL(skin) 1000ppm	Carbon Black Ethylene glycol Ethyl alcohol

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

Physical state and form	: Middle viscous liquid.
Color	: Black.
Odor	: Faint odor.
pH	: about 8.5
Boiling point	: Not available. [Water/ 100 C]
Melting point	: <-10 C
Flash point	: Not applicable. [2-Propanol/ 11.7 C]
Auto ignition temperature	: Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.
 [Lower flammable limit / 2.0% , Upper flammable limit / 12.7 % <2-Propanol>]
 Density : about 1.1 / 25 C
 Vapor density (air=1) : Not available. [2-Propanol/ 2.07-2.10]
 Solubility in water : Soluble.
 Evaporation rate : Not available.
 Volatile : 78-81%

10. STABILITY AND REACTIVITY

Stability : Stability.
 Hazardous reactions : Will not occur.
 Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.
 Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)
 oxidizing materials, halogens Carbon Black
 oxidizing materials Resin
 oxidizing materials, bases, acids, reducing agents, metals Ethylene glycol
 halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials Ethyl alcohol
 acids, metals, oxidizing materials, combustible materials, halogens, peroxides, bases, metal salts 2-Propanol

Hazardous decomposition products : (Information of components.)
 oxides of carbon, water common decomposition products
 sulfur compounds Carbon Black

11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>10000mg/kg-Rat	Carbon Black
	1650mg/kg-Cat, 4700mg/kg-Rat 3450mg/kg-Mouse 3600mg/kg-Mouse	Ethylene glycol Ethyl alcohol 2-Propanol
Inhalation LC50	20000ppm-10H-Rat 11100ppm-4H-Mouse	Ethyl alcohol 2-Propanol
Skin LD50	>3000mg/kg-Rabbit	Carbon Black
	9530uL/kg-Rabbit 12800mg/kg-Rabbit	Ethylene glycol 2-Propanol

Local effects
 Irritant:inhalation, skin Carbon Black
 Irritant:inhalation, skin, eye Ethylene glycol / Ethyl alcohol
 Irritant:inhalation, eye 2-Propanol

Chronic toxicity and long term toxicity

Lungs may be affected by repeated or prolonged exposure at very high concentrations. Respiratory disorders.

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note

The liquid defats the skin.

Carbon Black

Ethylene glycol

Ethyl alcohol

2-Propanol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation irritation,cough irritation,nausea	Carbon Black / Resin Ethylene glycol / Ethyl alcohol 2-Propanol
Skin contact	irritation irritation,dry irritation,absorption	Carbon Black / Resin Ethylene glycol / Ethyl alcohol 2-Propanol
Eye contact	mechanical irritation, discoloration of lids irritation irritation,redness irritation,pain	Carbon Black Resin Ethylene glycol / Ethyl alcohol 2-Propanol
Ingestion	nausea,vomiting rash,vomiting nausea,stomach pain	Ethylene glycol Ethyl alcohol 2-Propanol
Specific effects	IARC Group 2B IARC Group 3	Carbon Black 2-Propanol

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Carbon Black / Ethylene glycol / Ethyl alcohol / 2-Propanol

EU labeling

25%<=Xn;R22

F;R11

F;R11, Xi;R36

Ethylene glycol

Ethyl alcohol

2-Propanol

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over

0.1%over

Carbon Black / Ethylene glycol / 2-Propanol

Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.

The information contained in this sheet are based knowledge of the products at the data : (March 18, 2009). They are given quite sincerely.

Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Red [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : March 18, 2009

File No. : 010276A Rev. 2.5.08.03

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Titanium dioxide	13463-67-7	Registered	2366755	10- 30
Coloring agent	Registered	Registered	Registered	< 10
Resins	Registered	Registered	Registered	< 10
Ethylene glycol	107-21-1	Registered	2034733	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 37.4g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire.

Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

: Keep out of the reach of children.

: Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice : Not available.

Storage:

- Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.
- Storage condition : Avoid direct sunlight.
: Do not leave the products in high temperature space.
: Recommended temperature: 0-30 C.
- Incompatible products : (Information of components.)
- | | |
|--|------------------------|
| metals | Titanium dioxide |
| oxidizing materials | Coloring agent / Resin |
| oxidizing materials, bases, acids, | Ethylene glycol |
| reducing agents, metals | |
| halo carbons, metals, metal salts, | Ethyl alcohol |
| oxidizing materials, halogens, | |
| peroxides, acids, metal oxides, bases, | |
| combustible materials | |
- Packaging materials : Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	15mg/m3 TWA (Total dust)	Titanium dioxide
	1000ppm TWA	Ethyl alcohol
ACGIH	10mg/m3 TWA	Titanium dioxide
	100mg/m3 ceiling (particulate)(aerosol)	Ethylene glycol
	1000ppm TWA	Ethyl alcohol
EC	6mg/m3	Titanium dioxide
	52mg/m3(20ppm) TWA(skin),	Ethylene glycol
	104mg/m3(40ppm) STEL(skin)	
	1000ppm	Ethyl alcohol

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

- Physical state and form : Middle viscous liquid.
- Color : Red.
- Odor : Faint odor.
- pH : about 8.2
- Boiling point : Not available. [Water/ 100 C]
- Melting point : <-10 C
- Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)]
- Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]
- Explosion limits : Not applicable.
[Lower flammable limit / 3.28% , Upper flammable limit / 19.0% <Ethyl alcohol>]
- Density : about 1.1 / 25 C
- Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]
- Solubility in water : Soluble.
- Evaporation rate : Not available.
- Volatile : 72-75%

10. STABILITY AND REACTIVITY

Stability	: Stability.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.
Materials to avoid	: (Information of components.)
metals	Titanium dioxide
oxidizing materials	Coloring agent / Resin
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials	Ethyl alcohol
Hazardous decomposition products	: (Information of components.)
oxides of carbon, water	common decomposition products
oxides of titanium.	Titanium dioxide
oxides of nitrogen.	Coloring agent
miscellaneous decomposition products.	Resin

11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>24000mg/kg-Rat 1650mg/kg-Cat, 4700mg/kg-Rat 3450mg/kg-Mouse	Titanium dioxide Ethylene glycol Ethyl alcohol
Inhalation LC50	6820mg/m ³ -4H-Rat 20000ppm-10H-Rat	Titanium dioxide Ethyl alcohol
Skin LD50	9530uL/kg-Rabbit	Ethylene glycol

Local effects Irritant; inhalation, skin, eye Ethylene glycol / Ethyl alcohol

Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).	Ethylene glycol
The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note	Ethyl alcohol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation, cough	Titanium dioxide / Ethylene glycol / Ethyl alcohol
	irritation	Coloring agent
	headache, nausea	Resin

Skin contact	redness,swelling of skin irritation irritation,dry	Coloring agent Resin Ethylene glycol / Ethyl alcohol
Eye contact	irritation,redness irritation	Titanium dioxide / Ethylene glycol / Ethyl alcohol Resin
Ingestion	physiologically inert, intestinal obstruction nausea,vomiting digestive discomfort nausea,vomiting rash,vomiting	Titanium dioxide Coloring agent Resin Ethylene glycol Ethyl alcohol
Specific effects	IARC Group 2B	Titanium dioxide

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling

25%≤Xn;R22

Ethylene glycol

F;R11

Ethyl alcohol

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over

Ethylene glycol

0.1%over

Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.
The information contained in this sheet are based knowledge of the products
at the data : (March 18, 2009). They are given quite sincerely.
Moreover the attention of the users is drawn on the risks possibly taken,
when a product is used for other utilization than these which it is intended.

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Blue [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : March 18, 2009

File No. : 010277A Rev. 2.5.06.03

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Titanium dioxide	13463-67-7	Registered	2366755	10- 30
Resins	Registered	Registered	Registered Polymer	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10
2-Propanol	67-63-0	Registered	2006617	< 10
Coloring agents	Registered	Registered	Registered	< 10
Ethylene glycol	107-21-1	Registered	2034733	< 10
Silica (amorphous)	7631-86-9	Registered	2315454	< 10
Additive	Registered	Registered	Registered	< 10

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Resin / Coloring agent>

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

<2-Propanol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, eye irritation, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 40.8g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.
Use extinguishing agents appropriate for surrounding fire.
Avoid inhalation of material or combustion by-products.
Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.
: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.
: Recap after use.
: Keep out of the reach of children.
: Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

Storage condition	high temperature.
	: Avoid direct sunlight.
	: Do not leave the products in high temperature space.
	: Recommended temperature: 0-30 C.
Incompatible products	: (Information of components.)
metals	Titanium dioxide
oxidizing materials	Resin / Coloring agent
halo carbons, metals, metal salts,	Ethyl alcohol
oxidizing materials, halogens,	
peroxides, acids, metal oxides, bases,	
combustible materials	
acids, metals, oxidizing materials,	2-Propanol
combustible materials, halogens,	
peroxides, bases, metal salts	
oxidizing materials, bases, acids,	Ethylene glycol
reducing agents, metals	
halogens, acids, combustible materials,	Silica (amorphous)
metals, metal salts, oxidizing materials	

Packaging materials : Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	15mg/m3 TWA (Total dust)	Titanium dioxide
	1000ppm TWA	Ethyl alcohol
	400 ppm TWA, 500ppm STEL	2-Propanol
	5mg/m3(Respirable fraction),	Coloring agent
	15mg/m3(Total dust) [Nuisance Dust]	
	5mg/m3(as Mo), 1mg/m3(as W)	
ACGIH	[Soluble compounds]	
	20mppcf TWA (<1% crystalline silica)	Silica (amorphous)
	10mg/m3 TWA	Titanium dioxide /
		Coloring agent
	1000ppm TWA	Ethyl alcohol
	200ppm TWA, 400ppm STEL	2-Propanol
EC	5mg/m3(as Mo), 1mg/m3(as W)	Coloring agent
	[Soluble compounds]	
	100mg/m3 ceiling (particulate)(aerosol)	Ethylene glycol
	6mg/m3	Titanium dioxide
	1000ppm	Ethyl alcohol
	52mg/m3(20ppm) TWA(skin),	Ethylene glycol
	104mg/m3(40ppm) STEL(skin)	

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

Physical state and form	: Middle viscous liquid.
Color	: Blue.
Odor	: Faint odor.
pH	: about 8.4
Boiling point	: Not available. [Water/ 100 C]
Melting point	: <-10 C
Flash point	: Not applicable. [2-Propanol/ 11.7 C]
Auto ignition temperature	: Not applicable. [Ethyl alcohol/ 363 C]
Explosion limits	: Not applicable. [Lower flammable limit / 2.0% , Upper flammable limit / 12.7 % <2-Propanol>]
Density	: about 1.2 / 25 C
Vapor density (air=1)	: Not available. [2-Propanol/ 2.07-2.10]
Solubility in water	: Soluble.
Evaporation rate	: Not available.
Volatile	: 63-66%

10. STABILITY AND REACTIVITY

Stability : Stability.

Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.
Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

metals	Titanium dioxide
oxidizing materials	Resin / Coloring agent
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials	Ethyl alcohol
acids, metals, oxidizing materials, combustible materials, halogens, peroxides, bases, metal salts	2-Propanol
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
halogens, acids, combustible materials, metals, metal salts, oxidizing materials	Silica (amorphous)

Hazardous decomposition products : (Information of components.)

oxides of carbon, water	common decomposition products
oxides of titanium.	Titanium dioxide
oxides of nitrogen.	Coloring agent
crystalline silica.	Silica (amorphous)

11.TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>24000mg/kg-Rat 3450mg/kg-Mouse 3600mg/kg-Mouse ≥5000mg/kg-Rat 1650mg/kg-Cat、 4700mg/kg-Rat 3160mg/kg-Rat	Titanium dioxide Ethyl alcohol 2-Propanol Coloring agent Ethylene glycol Silica (amorphous)
Inhalation LC50	6820mg/m ³ -4H-Rat 20000ppm-10H-Rat 11100ppm-4H-Mouse	Titanium dioxide Ethyl alcohol 2-Propanol
Skin LD50	12800mg/kg-Rabbit 9530uL/kg-Rabbit	2-Propanol Ethylene glycol

Local effects	Irritant; inhalation, skin, eye Irritant; inhalation, eye	Ethyl alcohol / Ethylene glycol 2-Propanol
---------------	--	---

Chronic toxicity and long term toxicity

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note

Ethyl alcohol

The liquid defats the skin.

2-Propanol

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

Ethylene glycol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation,cough irritation irritation,nausea	Titanium dioxide / Ethyl alcohol / Ethylene glycol / Silica Resin / Coloring agent 2-Propanol
Skin contact	irritation irritation,dry irritation,absorption	Resin Ethyl alcohol / Ethylene glycol / Silica (amorphous) 2-Propanol
Eye contact	irritation,redness irritation irritation,pain	Titanium dioxide / Ethyl alcohol / Ethylene glycol / Silica Resin / Coloring agent 2-Propanol
Ingestion	physiologically inert, intestinal obstruction rash,vomiting nausea,stomach pain gastric disturbances nausea,vomiting	Titanium dioxide Ethyl alcohol 2-Propanol Coloring agent Ethylene glycol

Specific effects	IARC Group 2B IARC Group 3	Titanium dioxide 2-Propanol / Silica (amorphous)
------------------	-------------------------------	---

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

\ : Titanium dioxide / Ethyl alcohol / 2-Propanol / Ethylene glycol

EU labeling

F;R11

Ethyl alcohol

F;R11, Xi;R36

2-Propanol

25%<=Xn;R22

Ethylene glycol

CANADA Hazardous Products Act - Ingredient Disclosure List

0.1%over

Ethyl alcohol

1%over

2-Propanol / Ethylene glycol / Silica (amorphous)

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.

The information contained in this sheet are based knowledge of the products at the data : (March 18, 2009). They are given quite sincerely.

Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Green [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : March 18, 2009

File No. : 010278A Rev. 2.5.07.03

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Titanium dioxide	13463-67-7	Registered	2366755	10- 30
Resins	Registered	Registered	Registered	< 10
Coloring agents	Registered	Registered	Registered	< 10
Ethylene glycol	107-21-1	Registered	2034733	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Coloring agent>

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 38.8g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire.

Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

: Keep out of the reach of children.

: Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice : Not available.

Storage:

- Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.
- Storage condition : Avoid direct sunlight.
: Do not leave the products in high temperature space.
: Recommended temperature: 0-30 C.
- Incompatible products : (Information of components.)
- | | |
|--|------------------------|
| metals | Titanium dioxide |
| oxidizing materials | Resin / Coloring agent |
| oxidizing materials, bases, acids, reducing agents, metals | Ethylene glycol |
| halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials | Ethyl alcohol |
- Packaging materials : Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	15mg/m3 TWA (Total dust)	Titanium dioxide / Coloring agent
	1000ppm TWA	Ethyl alcohol
ACGIH	10mg/m3 TWA	Titanium dioxide / Coloring agent
	100mg/m3 ceiling (particulate)(aerosol)	Ethylene glycol
	1000ppm TWA	Ethyl alcohol
EC	6mg/m3	Titanium dioxide
	52mg/m3(20ppm) TWA(skin),	Ethylene glycol
	104mg/m3(40ppm) STEL(skin)	
	1000ppm	Ethyl alcohol

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

- Physical state and form : Middle viscous liquid.
- Color : Green.
- Odor : Faint odor.
- pH : about 8.2
- Boiling point : Not available. [Water/ 100 C]
- Melting point : <-10 C
- Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)]
- Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]
- Explosion limits : Not applicable.
[Lower flammable limit / 3.28% , Upper flammable limit / 19.0% <Ethyl alcohol>]
- Density : about 1.1 / 25 C
- Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]

Solubility in water : Soluble.
Evaporation rate : Not available.
Volatile : 73-76%

10. STABILITY AND REACTIVITY

Stability : Stability.
Hazardous reactions : Will not occur.
Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.
Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

metals	Titanium dioxide
oxidizing materials	Resin / Coloring agent
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials	Ethyl alcohol

Hazardous decomposition products : (Information of components.)

oxides of carbon, water	common decomposition products
oxides of titanium.	Titanium dioxide
miscellaneous decomposition products.	Resin
cyanide, oxides of nitrogen, miscellaneous decomposition products.	Coloring agent

11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>24000mg/kg-Rat ≥5000mg/kg-Rat 1650mg/kg-Cat、 4700mg/kg-Rat 3450mg/kg-Mouse	Titanium dioxide Coloring agent Ethylene glycol Ethyl alcohol
Inhalation LC50	6820mg/m ³ -4H-Rat 20000ppm-10H-Rat	Titanium dioxide Ethyl alcohol
Skin LD50	9530uL/kg-Rabbit	Ethylene glycol

Local effects Irritant; inhalation, skin, eye Ethylene glycol / Ethyl alcohol

Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).	Ethylene glycol
The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note	Ethyl alcohol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation,cough headache,nausea irritation	Titanium dioxide / Ethylene glycol / Ethyl alcohol Resin Coloring agent
Skin contact	irritation irritation,dry	Resin / Coloring agent Ethylene glycol / Ethyl alcohol
Eye contact	irritation,redness irritation	Titanium dioxide / Ethylene glycol / Ethyl alcohol Resin / Coloring agent
Ingestion	physiologically inert, intestinal obstruction digestive discomfort nausea,vomiting rash,vomiting	Titanium dioxide Resin Coloring agent / Ethylene glycol Ethyl alcohol
Specific effects	IARC Group 2B	Titanium dioxide

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling

Xi;R43

Coloring agent

25%≤Xn;R22

Ethylene glycol

F;R11

Ethyl alcohol

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over

Ethylene glycol

0.1%over

Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.
The information contained in this sheet are based knowledge of the products
at the data : (March 18, 2009). They are given quite sincerely.
Moreover the attention of the users is drawn on the risks possibly taken,
when a product is used for other utilization than these which it is intended.

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Yellow [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : March 18, 2009

File No. : 010279A Rev. 2.5.07.03

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Titanium dioxide	13463-67-7	Registered	2366755	< 10
Coloring agents	Registered	Registered	Registered	< 10
Resins	Registered	Registered	Registered	< 10
Ethylene glycol	107-21-1	Registered	2034733	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Coloring agent>

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 38.1g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire.

Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.
: Recap after use.
: Keep out of the reach of children.
: Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.

Storage condition : Avoid direct sunlight.
: Do not leave the products in high temperature space.
: Recommended temperature: 0-30 C.

Incompatible products : (Information of components.)

metals	Titanium dioxide
oxidizing materials	Coloring agent / Resin
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases,	Ethyl alcohol

Packaging materials : Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	15mg/m3 TWA (Total dust)	Titanium dioxide Coloring agent
	5mg/m3(Respirable fraction),	
	15mg/m3(Total dust) [Nuisance Dust]	
	1000ppm TWA	Ethyl alcohol
ACGIH	10mg/m3 TWA	Titanium dioxide / Coloring agent Ethylene glycol Ethyl alcohol
	100mg/m3 ceiling (particulate)(aerosol)	
	1000ppm TWA	
	6mg/m3	Titanium dioxide
EC	52mg/m3(20ppm) TWA(skin),	Ethylene glycol
	104mg/m3(40ppm) STEL(skin)	
	1000ppm	Ethyl alcohol

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

Physical state and form : Middle viscous liquid.
Color : Yellow.
Odor : Faint odor.
pH : about 8.3
Boiling point : Not available. [Water/ 100 C]
Melting point : <-10 C
Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)]
Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]
Explosion limits : Not applicable.
[Lower flammable limit / 3.28% , Upper flammable limit / 19.0% <Ethyl alcohol>]
Density : about 1.1 / 25 C
Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]
Solubility in water : Soluble.
Evaporation rate : Not available.
Volatile : 74-77%

10. STABILITY AND REACTIVITY

Stability	: Stability.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.
Materials to avoid	: (Information of components.)
metals	Titanium dioxide
oxidizing materials	Coloring agent / Resin
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials	Ethyl alcohol
Hazardous decomposition products	: (Information of components.)
oxides of carbon, water	common decomposition products
oxides of titanium.	Titanium dioxide
oxides of nitrogen, miscellaneous decomposition products.	Coloring agent
miscellaneous decomposition products.	Resin

11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>24000mg/kg-Rat ≥ 5000mg/kg-Rat 1650mg/kg-Cat、 4700mg/kg-Rat 3450mg/kg-Mouse	Titanium dioxide Coloring agent Ethylene glycol Ethyl alcohol
Inhalation LC50	6820mg/m ³ -4H-Rat 20000ppm-10H-Rat	Titanium dioxide Ethyl alcohol
Skin LD50	9530uL/kg-Rabbit	Ethylene glycol

Local effects Irritant;inhalation, skin, eye Ethylene glycol / Ethyl alcohol

Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).	Ethylene glycol
The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note	Ethyl alcohol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation,cough irritation headache,nausea	Titanium dioxide / Ethylene glycol / Ethyl alcohol Coloring agent Resin
Skin contact	redness,swelling irritation irritation,dry	Coloring agent Resin Ethylene glycol / Ethyl alcohol
Eye contact	irritation,redness irritation	Titanium dioxide / Ethylene glycol / Ethyl alcohol Resin
Ingestion	physiologically inert, intestinal obstruction nausea,vomiting digestive discomfort rash,vomiting	Titanium dioxide Coloring agent / Ethylene glycol Resin Ethyl alcohol
Specific effects	IARC Group 2B	Titanium dioxide

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling

Xi;R43

Coloring agent

25%≤Xn;R22

Ethylene glycol

F;R11

Ethyl alcohol

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over

Ethylene glycol

0.1%over

Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.
The information contained in this sheet are based knowledge of the products
at the data : (March 18, 2009). They are given quite sincerely.
Moreover the attention of the users is drawn on the risks possibly taken,
when a product is used for other utilization than these which it is intended.

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Pink [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : June 1, 2009

File No. : 010280A Rev. 2.5.07.04

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Titanium dioxide	13463-67-7	Registered	2366755	10- 30
Resins	Registered	Registered	Registered	10- 30
Ethylene glycol	107-21-1	Registered	2034733	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10
Coloring agents	Registered	Registered	Registered	< 10
Polyoxyethylene nonylphenyl ether	9016-45-9	Registered	Registered	< 1

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Resin>

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 39.4g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire.

Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.
: Recap after use.
: Keep out of the reach of children.
: Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

: Recommended temperature: 0-30 C.

Incompatible products : (Information of components.)

metals

oxidizing materials

oxidizing materials, bases, acids, reducing agents, metals

halo carbons, metals, metal salts, oxidizing materials,

halogens, peroxides, acids, metal oxides, bases,

combustible materials

Titanium dioxide

Resin / Coloring agent /

Polyoxyethylene nonylphenyl ether

Ethylene glycol

Ethyl alcohol

Packaging materials : Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	15mg/m3 TWA	Titanium dioxide /
	1000ppm TWA	Coloring agent
ACGIH	10mg/m3 TWA	Ethyl alcohol
	1000ppm TWA	Titanium dioxide /
	100mg/m3 ceiling (particulate)(aerosol)	Coloring agent
EC	6mg/m3	Ethyl alcohol
	52mg/m3(20ppm) TWA(skin),	Ethylene glycol
	104mg/m3(40ppm) STEL(skin)	Titanium dioxide
	1000ppm	Ethylene glycol
		Ethyl alcohol

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

Physical state and form : Low viscous liquid.

Color : Pink.

Odor : Faint odor.

pH : about 8.0

Boiling point : Not available. [Water/ 100 C]

Melting point : <-10 C

Flash point : Not applicable. [Ethyl alcohol/ 12.2 C(CC)]

Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.

[Lower flammable limit / 3.28% , Upper flammable limit / 19.0% <Ethyl alcohol>]

Density : about 1.2 / 25 C

Vapor density (air=1) : Not available. [Ethyl alcohol/ 1.59]

Solubility in water : Soluble.

Evaporation rate : Not available.

Volatile : 68-71%

10. STABILITY AND REACTIVITY

Stability : Stability.

Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.
Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

metals	Titanium dioxide
oxidizing materials	Resin / Coloring agent / Polyoxyethylene nonylphenyl ether
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
halo carbons, metals, metal salts, oxidizing materials,	Ethyl alcohol
halogens, peroxides, acids, metal oxides, bases,	
combustible materials	

Hazardous decomposition products : (Information of components.)

oxides of carbon, water	common decomposition products
oxides of titanium.	Titanium dioxide
oxides of nitrogen, cyanides, aldehydes,	Resin
corrosive acrolein, various organic fragments,	
miscellaneous decomposition products.	
oxides of nitrogen.	Coloring agent

11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>24000mg/kg-Rat 1000mg/kg-Mouse 1650mg/kg-Cat, 4700mg/kg-Rat 3450mg/kg-Mouse 2950mg/kg-Mouse 1310mg/kg-Rat	Titanium dioxide Resin Ethylene glycol Ethyl alcohol Coloring agent Polyoxyethylene nonylphenyl ether
Inhalation LC50	6820mg/m ³ -4H-Rat 20000ppm-10H-Rat	Titanium dioxide Ethyl alcohol
Skin LD50	9530uL/kg-Rabbit 2ml/kg-Rabbit	Ethylene glycol Polyoxyethylene nonylphenyl ether

Local effects	Irritant;inhalation, skin, eye Irritant;eye	Ethylene glycol / Ethyl alcohol Polyoxyethylene nonylphenyl ether
---------------	--	--

Chronic toxicity and long term toxicity

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).	Ethylene glycol
The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note.	Ethyl alcohol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation,cough irritation	Titanium dioxide / Resin / Ethylene glycol / Ethyl alcohol Coloring agent / Polyoxyethylene nonylphenyl ether
Skin contact	mechanical abrasion,irritation irritation,dry redness,swelling of skin irritation	Resin Ethylene glycol / Ethyl alcohol Coloring agent Polyoxyethylene nonylphenyl ether
Eye contact	irritation,redness irritation irritation,eye damage	Titanium dioxide / Ethylene glycol / Ethyl alcohol Resin Polyoxyethylene nonylphenyl ether
Ingestion	physiologically inert,intestinal digestive discomfort nausea,vomiting rash,vomiting digestive disorders,diarrhea	Titanium dioxide Resin Ethylene glycol / Coloring agent Ethyl alcohol Polyoxyethylene nonylphenyl ether
Specific effects	IARC Group 2B IARC Group 3	Titanium dioxide Resin

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Titanium dioxide / Ethylene glycol / Ethyl alcohol

EU labeling

25%≤Xn;R22

Ethylene glycol

F;R11

Ethyl alcohol

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over

Ethylene glycol

0.1%over

Ethyl alcohol

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.
The information contained in this sheet are based knowledge of the products
at the data : (June 1, 2009). They are given quite sincerely.
Moreover the attention of the users is drawn on the risks possibly taken,
when a product is used for other utilization than these which it is intended.

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K Light blue [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : March 18, 2009

File No. : 010281A Rev. 2.5.07.03

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Titanium dioxide	13463-67-7	Registered	2366755	10- 30
Resins	Registered	Registered	Registered	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10
Ethylene glycol	107-21-1	Registered	2034733	< 10
2-Propanol	67-63-0	Registered	2006617	< 10
Coloring agent	Registered	Registered	Registered	< 10

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

<2-Propanol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, eye irritation, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

<Coloring agent>

PHYSICAL HAZARDS: Dust/air mixtures may ignite or explode.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 41.8g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire.

Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Recap after use.

: Keep out of the reach of children.

: Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.

Storage condition	: Avoid direct sunlight.
	: Do not leave the products in high temperature space.
	: Recommended temperature: 0-30 C.
Incompatible products	: (Information of components.)
metals	Titanium dioxide
oxidizing materials	Resin / Coloring agent
halo carbons, metals, metal salts,	Ethyl alcohol
oxidizing materials, halogens,	
peroxides, acids, metal oxides, bases,	
combustible materials	
oxidizing materials, bases, acids,	Ethylene glycol
reducing agents, metals	
acids, metals, oxidizing materials,	2-Propanol
combustible materials, halogens,	
peroxides, bases, metal salts	
Packaging materials	: Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	15mg/m3 TWA (Total dust) 1000ppm TWA 400 ppm TWA, 500ppm STEL 5mg/m3(Respirable fraction), 15mg/m3(Total dust) [Nuisance Dust]	Titanium dioxide Ethyl alcohol 2-Propanol Coloring agent
ACGIH	10mg/m3 TWA 1000ppm TWA 100mg/m3 ceiling (particulate)(aerosol) 200ppm TWA, 400ppm STEL	Titanium dioxide / Coloring agent Ethyl alcohol Ethylene glycol 2-Propanol
EC	6mg/m3 1000ppm 52mg/m3(20ppm) TWA(skin), 104mg/m3(40ppm) STEL(skin)	Titanium dioxide Ethyl alcohol Ethylene glycol

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

Physical state and form	: Middle viscous liquid.
Color	: Light blue.
Odor	: Faint odor.
pH	: about 8.4
Boiling point	: Not available. [Water/ 100 C]
Melting point	: <-10 C
Flash point	: Not applicable. [2-Propanol/ 11.7 C]
Auto ignition temperature	: Not applicable. [Ethyl alcohol/ 363 C]
Explosion limits	: Not applicable.
[Lower flammable limit / 2.0% , Upper flammable limit / 12.7 % <2-Propanol>]	

Density	: about 1.2 / 25 C
Vapor density (air=1)	: Not available. [2-Propanol/ 2.07-2.10]
Solubility in water	: Soluble.
Evaporation rate	: Not available.
Volatile	: 69-72%

10. STABILITY AND REACTIVITY

Stability	: Stability.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

metals	Titanium dioxide
oxidizing materials	Resin / Coloring agent
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials	Ethyl alcohol
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
acids, metals, oxidizing materials, combustible materials, halogens, peroxides, bases, metal salts	2-Propanol

Hazardous decomposition products : (Information of components.)

oxides of carbon, water	common decomposition products
oxides of titanium.	Titanium dioxide
miscellaneous decomposition products.	Resin
oxides of nitrogen.	Coloring agent

11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>24000mg/kg-Rat 3450mg/kg-Mouse 1650mg/kg-Cat、 4700mg/kg-Rat 3600mg/kg-Mouse >5000mg/kg-Rat	Titanium dioxide Ethyl alcohol Ethylene glycol 2-Propanol Coloring agent
Inhalation LC50	6820mg/m ³ -4H-Rat 20000ppm-10H-Rat 11100ppm-4H-Mouse	Titanium dioxide Ethyl alcohol 2-Propanol
Skin LD50	9530uL/kg-Rabbit 12800mg/kg-Rabbit	Ethylene glycol 2-Propanol

Local effects	Irritant:inhalation, skin, eye Irritant:inhalation, eye	Ethyl alcohol / Ethylene glycol 2-Propanol
---------------	--	---

Chronic toxicity and long term toxicity

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note

Ethyl alcohol

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

Ethylene glycol

The liquid defats the skin.

2-Propanol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation,cough headache,nausea irritation,nausea irritation	Titanium dioxide / Ethyl alcohol / Ethylene glycol Resin 2-Propanol Coloring agent
Skin contact	irritation irritation,dry irritation,absorption	Resin Ethyl alcohol / Ethylene glycol 2-Propanol
Eye contact	irritation,redness irritation irritation,pain	Titanium dioxide / Ethyl alcohol / Ethylene glycol Resin / Coloring agent 2-Propanol
Ingestion	physiologically inert, intestinal obstruction digestive discomfort rash,vomiting nausea,vomiting nausea,stomach pain gastric disturbances	Titanium dioxide Resin Ethyl alcohol Ethylene glycol 2-Propanol Coloring agent
Specific effects	IARC Group 2B IARC Group 3	Titanium dioxide 2-Propanol

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Titanium dioxide / Ethyl alcohol / Ethylene glycol / 2-Propanol

EU labeling

F;R11

Ethyl alcohol

25%≤Xn;R22

Ethylene glycol

F;R11, Xi;R36

2-Propanol

CANADA Hazardous Products Act - Ingredient Disclosure List

0.1%over

Ethyl alcohol

1%over

Ethylene glycol / 2-Propanol

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.

The information contained in this sheet are based knowledge of the products at the data : (March 18, 2009). They are given quite sincerely.

Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: PC-17K White [POSCA]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN

Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 24, 2001

Revision Date : March 18, 2009

File No. : 010282A Rev. 2.5.07.03

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation : Preparation

Chemical nature:

Component parts : Ink

Chemical or generic name	CAS No.	TSCA	EINECS No.	Concentration range (wt%)
Water	7732-18-5	Registered	2317912	50- 80
Titanium dioxide	13463-67-7	Registered	2366755	10- 30
Resins	Registered	Registered	Registered	< 10
Ethyl alcohol	64-17-5	Registered	2005786	< 10
Ethylene glycol	107-21-1	Registered	2034733	< 10
2-Propanol	67-63-0	Registered	2006617	< 10

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available.

Specific hazards : Information of components.

<Ethyl alcohol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, liver damage, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

<Ethylene glycol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, skin irritation, eye irritation, central nervous system depression, nerve damage, kidney damage

<2-Propanol>

MAJOR HEALTH HAZARDS: respiratory tract irritation, eye irritation, central nervous system depression

PHYSICAL HAZARDS: Flammable liquid and vapor. Vapor may cause flash fire.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of product : about 42.8g]

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : The Products is no flammable.

Use extinguishing agents appropriate for surrounding fire.

Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions : Do not wash away into shower or water way.

Methods for cleaning up : Wipe off by dry cloth and wash with water.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.
: Recap after use.
: Keep out of the reach of children.
: Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice : Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and high temperature.

Storage condition : Avoid direct sunlight.
: Do not leave the products in high temperature space.
: Recommended temperature: 0-30 C.

Incompatible products : (Information of components.)

metals	Titanium dioxide
oxidizing materials	Resin
halo carbons, metals, metal salts,	Ethyl alcohol
oxidizing materials, halogens,	
peroxides, acids, metal oxides, bases,	
combustible materials	
oxidizing materials, bases, acids,	Ethylene glycol
reducing agents, metals	
acids, metals, oxidizing materials,	2-Propanol
combustible materials, halogens,	
peroxides, bases, metal salts	

Packaging materials : Not applicable.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

OSHA	15mg/m3 TWA (Total dust) 1000ppm TWA 400 ppm TWA, 500ppm STEL	Titanium dioxide Ethyl alcohol 2-Propanol
ACGIH	10mg/m3 TWA 1000ppm TWA 100mg/m3 ceiling (particulate)(aerosol) 200ppm TWA, 400ppm STEL	Titanium dioxide Ethyl alcohol Ethylene glycol 2-Propanol
EC	6mg/m3 1000ppm 52mg/m3(20ppm) TWA(skin), 104mg/m3(40ppm) STEL(skin)	Titanium dioxide Ethyl alcohol Ethylene glycol

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[] : Information of components.

Physical state and form : Middle viscous liquid.

Color : White.

Odor : Faint odor.

pH : about 8.1

Boiling point : Not available. [Water/ 100 C]

Melting point : <-10 C

Flash point : Not applicable. [2-Propanol/ 11.7 C]

Auto ignition temperature : Not applicable. [Ethyl alcohol/ 363 C]

Explosion limits : Not applicable.
[Lower flammable limit / 2.0% , Upper flammable limit / 12.7 % <2-Propanol>]

Density : about 1.3 / 25 C

Vapor density (air=1) : Not available. [2-Propanol/ 2.07-2.10]

Solubility in water : Soluble.

Evaporation rate : Not available.
Volatile : 65-68%

10. STABILITY AND REACTIVITY

Stability : Stability.
Hazardous reactions : Will not occur.
Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.
Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

metals	Titanium dioxide
oxidizing materials	Resin
halo carbons, metals, metal salts, oxidizing materials, halogens, peroxides, acids, metal oxides, bases, combustible materials	Ethyl alcohol
oxidizing materials, bases, acids, reducing agents, metals	Ethylene glycol
acids, metals, oxidizing materials, combustible materials, halogens, peroxides, bases, metal salts	2-Propanol

Hazardous decomposition products : (Information of components.)

oxides of carbon, water	common decomposition products
oxides of titanium.	Titanium dioxide
miscellaneous decomposition products.	Resin

11. TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

Ingestion LD50	>24000mg/kg-Rat 3450mg/kg-Mouse 1650mg/kg-Cat、 4700mg/kg-Rat 3600mg/kg-Mouse	Titanium dioxide Ethyl alcohol Ethylene glycol 2-Propanol
Inhalation LC50	6820mg/m ³ -4H-Rat 20000ppm-10H-Rat 11100ppm-4H-Mouse	Titanium dioxide Ethyl alcohol 2-Propanol
Skin LD50	9530uL/kg-Rabbit 12800mg/kg-Rabbit	Ethylene glycol 2-Propanol

Local effects	Irritant;inhalation, skin, eye Irritant;inhalation, eye	Ethyl alcohol / Ethylene glycol 2-Propanol
---------------	--	---

Chronic toxicity and long term toxicity

The liquid defats the skin. The substance may have effects on the upper respiratory tract and central nervous system, resulting in irritation, headache, fatigue and lack of concentration. See Note

Ethyl alcohol

The substance may have effects on the central nervous system, resulting in abnormal eye movements (nystagmus).

Ethylene glycol

The liquid defats the skin.

2-Propanol

Signs and Symptoms of overexposure and aggravated by exposure

Inhalation	irritation,cough headache,nausea irritation,nausea	Titanium dioxide / Ethyl alcohol / Ethylene glycol Resin 2-Propanol
Skin contact	irritation irritation,dry irritation,absorption	Resin Ethyl alcohol / Ethylene glycol 2-Propanol
Eye contact	irritation,redness irritation irritation,pain	Titanium dioxide / Ethyl alcohol / Ethylene glycol Resin 2-Propanol
Ingestion	physiologically inert, intestinal obstruction digestive discomfort rash,vomiting nausea,vomiting nausea,stomach pain	Titanium dioxide Resin Ethyl alcohol Ethylene glycol 2-Propanol
Specific effects	IARC Group 2B IARC Group 3	Titanium dioxide 2-Propanol

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging : Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960820

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS)

: Titanium dioxide / Ethyl alcohol / Ethylene glycol / 2-Propanol

EU labeling

F;R11

Ethyl alcohol

25%≤Xn;R22

Ethylene glycol

F;R11, Xi;R36

2-Propanol

CANADA Hazardous Products Act - Ingredient Disclosure List

0.1%over

Ethyl alcohol

1%over

Ethylene glycol / 2-Propanol

Hazard and safety information

Products are manufactured in accordance with European regulation EN71 part 3

Products are manufactured in accordance with ELV directive of EU.

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it.

The information contained in this sheet are based knowledge of the products at the data : (March 18, 2009). They are given quite sincerely.

Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.